

## MANOMÈTRE ENCASTRABLE BRIDE FIXE ARRIÈRE AXIAL - MN64

Ø	B	D	D1	H	G"	CH	Kg
40	25	39	43.3	41	R1/8	11	0.099
50	29	52	57	52	R1/4	14	0.145
63	29	62	68	50	G1/4	14	0.174

Référence/Code	Ø	Plage (bar) Range	Raccordement" Connection"	Précision Accuracy	
<b>MN644018099PS</b>	40	-1 ÷ 0	R1/8	CL2.5	1
<b>MN644018001PS</b>	40	0 ÷ 1	R1/8	CL2.5	1
<b>MN644018106PS</b>	40	0 ÷ 1.6	R1/8	CL2.5	1
<b>MN644018205PS</b>	40	0 ÷ 2.5	R1/8	CL2.5	1
<b>MN644018004PS</b>	40	0 ÷ 4	R1/8	CL2.5	1
<b>MN644018006PS</b>	40	0 ÷ 6	R1/8	CL2.5	1
<b>MN644018010PS</b>	40	0 ÷ 10	R1/8	CL2.5	1
<b>MN644018012PS</b>	40	0 ÷ 12	R1/8	CL2.5	1
<b>MN644018016PS</b>	40	0 ÷ 16	R1/8	CL2.5	1

<b>MN645014099PS</b>	50	-1 ÷ 0	R1/4	CL2.5	1
<b>MN645014001PS</b>	50	0 ÷ 1	R1/4	CL2.5	1
<b>MN645014106PS</b>	50	0 ÷ 1.6	R1/4	CL2.5	1
<b>MN645014205PS</b>	50	0 ÷ 2.5	R1/4	CL2.5	1
<b>MN645014004PS</b>	50	0 ÷ 4	R1/4	CL2.5	1
<b>MN645014006PS</b>	50	0 ÷ 6	R1/4	CL2.5	1
<b>MN645014010PS</b>	50	0 ÷ 10	R1/4	CL2.5	1
<b>MN645014012PS</b>	50	0 ÷ 12	R1/4	CL2.5	1
<b>MN645014016PS</b>	50	0 ÷ 16	R1/4	CL2.5	1
<b>MN645014025PS</b>	50	0 ÷ 25	R1/4	CL2.5	1

<b>MN644018099PS</b>	40	-1 ÷ 0	R1/8	CL2.5	1
<b>MN644018001PS</b>	40	0 ÷ 1	R1/8	CL2.5	1
<b>MN644018106PS</b>	40	0 ÷ 1.6	R1/8	CL2.5	1
<b>MN644018205PS</b>	40	0 ÷ 2.5	R1/8	CL2.5	1
<b>MN644018004PS</b>	40	0 ÷ 4	R1/8	CL2.5	1
<b>MN644018006PS</b>	40	0 ÷ 6	R1/8	CL2.5	1
<b>MN644018010PS</b>	40	0 ÷ 10	R1/8	CL2.5	1
<b>MN644018012PS</b>	40	0 ÷ 12	R1/8	CL2.5	1
<b>MN644018016PS</b>	40	0 ÷ 16	R1/8	CL2.5	1

