



RACCORD INSTANTANÉS HAUTE PRESSION «SPÉCIAL GRAISSAGE»

HDS 019 - RACCORD COUDÉ INSTANTANÉ FILETAGE CONIQUE

THREADED ELBOW MALE ADAPTOR CONICAL



Référence	ØD	R	H	L1	L2	
H190418	4	R1/8	8	17	23,5	10
H190406	4	M6x1	7	17	23,5	10
H190408	4	M8x1	7	17	23,5	10
H190410	4	M10x1	7	17	23,5	10
H190618	6	R1/8	8	20	27	11
H190606	6	M6x1	7	20	27	11
H190608	6	M8x1	7	20	27	11
H190610	6	M10x1	7	20	27	11

Plage de température	-40°C à +150°C	
Plage de pression	Jusqu'à 250 bar	Avec du tuyau adapté
Vide	max 98%	
Matériaux	Corps en laiton nickelé Joints HNBR Bague de butée laiton poli	CW614N & CW617N Sans silicone CW614N
Filetage	Filetage con. DIN EN 10226 (DIN 2999)	
Milieu	En contact d'huiles et graisses	
Tuyau	Dimensions recommandée : 4 mm = 4x1.5 6 mm = 6x3 Tolérances : ±0.05 mm	Matériaux recommandés : PTFE, ou tubes haute pression